



# NAIL TAG Unique

<b>Chip type:</b>	UNIQUE – read only 64bits			* Test conditions and remarks
<b>Physical:</b>	Diameter:	4 mm ± 0.3 mm		
	Length:	35 mm ± 0.5 mm		
	Material:	Polyamid with glass fiber		
	Color:	Black		
<b>Electrical:</b>	Operating frequency:	125 kHz	± 6 kHz	* At room temperature
<b>Chemical:</b>	Water immersion IP67			* 20°C, 35 min, 1 m
<b>Thermal:</b>	Storage:	-25°C to 85°C		
	Operating:	-25°C to 85°C		
<b>Part number:</b>	601901			* 1 x 1000h
<b>Remarks:</b>	Some very hard wood or other material may cause inserting problems and it may be necessary to drill a hole before insertion. Removing the part for re-use may cause damage.			

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.3.9 - 601901	Version : 2	Validation : 31.10.2001	By : PHH
Public Use	Accomplishment : Final	Status : Released	DefKey : 2845

